



SuperFlex Standard Lid 336 mm		Logical no: 2220
Dimensions		
Shape:	Round	
External diameter:	333 mm +/- 3 mm	
Height:	27,2 mm +/- 0,3 mm	
Closure type		
Closure type:	Flex-off	
Lid type:	Standard	
Decoration		
Decoration available:	Dry Offset	
Decoration area offset:	190 mm	
Raw material		
Raw material options:	PP	
Masterbatch colours:	Colours according to RPC Superfos standard selected pantone colours.	
Hot filling:	<p>The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures</p>	
Cold temperatures:	<p>Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures</p>	
Weight		
Weight:	133 g +/- 6 g	
Packing		
On pallet 1200x800:	NA pcs.	On pallet 1200x1000 600 pcs.
Number per layer:	NA pcs.	Number per layer: 10 pcs.
Height incl. pallet:	NA m	Height incl. pallet: 1,3 m
Stackability, empty:	NA pallets high	Stackability, empty: 2 pallets high
Quality Specifications		
Approvals:	<p>All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.</p>	
Shelf life:	<p>The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period</p>	
Quality information:	<p>Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.</p>	
Other		
UN approval:	No	
Special:		