

SuperLift Standard with centering pieces Lid 267 mm

Logical no: 4083

Dimensions

Shape: Round

External diameter: 265 mm +/- 2 mm Height: 13,3 mm +/- 0,5 mm

Closure type

Closure type: Peel-Off

Lid type: Standard with centering

Decoration

Decoration available: Dry Offset Decoration area offset: Ø 190 mm

Raw material

Raw material options:

Masterbatch colours: Colours according to RPC Superfos standard selected pantone colours.

Hot filling: The material chosen has a very good heat resistance and the packaging is suitable for hot filling.

Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must

be taken

in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by

the customer with the actual product before approval for use at hot temperatures

Cold temperatures:

Freezing conditions require special resins available on request.

The RPC Superfos packaging must be tested by the customer with the actual product before

approval for use at low temperatures

Weight

Weight: 60 g +/- 4 g

Packing

On pallet 1200x800: 2184 pcs. 1248 pcs. On pallet 800x1200 Number per layer: 12 pcs. Number per layer: 12 pcs. Height incl. pallet: Height incl. pallet: 1,15 m 0,92 m Stackability, empty: 2 pallets high Stackability, empty: 3 pallets high

Quality Specifications

Approvals: All RPC Superfos Products comply with the European Union Commission Regulation No.

10/2011/EC amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to

ensure that the supplied product is sutable for the intended use.

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 Shelf life:

months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per Quality information:

100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Other

UN approval: Nο

Special:

Specifications are subject to change without

Version 10.1

Latest revision: 30-04-2015