



SuperLift Standard with centering ring Lid 293 mm		Logical no:	4116
<b>Dimensions</b>			
Shape:	Round		
External diameter:	290,7 mm +/- 3 mm		
Height:	16,3 mm +/- 0,2 mm		
<b>Closure type</b>			
Closure type:	Peel-Off		
Lid type:	Standard with centering ring		
<b>Decoration</b>			
Decoration available:	Dry Offset		
Decoration area offset:	Ø 190 mm		
<b>Raw material</b>			
Raw material options:	PP		
Masterbatch colours:	Colours according to RPC Superfos standard selected pantone colours.		
Hot filling:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures		
Cold temperatures:	Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures		
<b>Weight</b>			
Weight:	90 g +/- 4 g		
<b>Packing</b>			
On pallet 1200x800:	990 pcs.	On pallet	NA pcs.
Number per layer:	11 pcs.	Number per layer:	NA pcs.
Height incl. pallet:	0,98 m	Height incl. pallet:	NA m
Stackability, empty:	3 pallets high	Stackability, empty:	NA pallets high
<b>Quality Specifications</b>			
Approvals:	All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period		
Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.		
<b>Other</b>			
UN approval:	No		
Special:			