





Technical Data Sheet

	<h3>SuperFlex ø336 mm 27,3 ltr</h3>	
	Logical no: 9270 Available lids: 2220 (standard), 2221 (TE), 2168 (membrane)	
Volume		
Volume under lid: 26,7 ltr +/- ml	Volume brimful: 27,3 ltr +/- ml	
Dimensions		
Shape: Round Conical External dia top without lid: 331,9 mm +/- 2 mm External dia top with lid: 333,7 mm +/- 2 mm	External diameter bottom: 286,2 mm +/- 2 mm Height without lid: 421,5 mm +/- 2 mm Height with std lid: 425,4 mm +/- 2 mm	
Weight		
Weight container/pot: 851 g +/- 12 g Weight standard lid: 133 g +/- 6 g	Weight plastic handle: 0 g +/- g Weight metal handle: 61 g +/- 4 g	
Performance		
Stackability - dynamic: Max: 50 kg Max top load on bottom container at 23°	UN approval: No	
Stacking tests:	Special: The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.	
Closure system		
Lid type options: Membrane, Standard, Tamper Evidence Closure type: Flex-off Protective collar: No Tamper Evidence type: None	Handle Handle available: Body Grip, Standard steel with roller grip	
Decoration		
Decoration available: Dry Offset, IML	Decoration area offset: 925 x 250 mm without overlap	
Packing		
On pallet 1200x800: NA pcs. Pieces per layer: NA pcs.	On pallet 1320x1000: 240 pcs. Pieces per layer: 12 pcs.	
Height incl. pallet: NA m Stackability, empty: NA pallets high	Height incl. pallet: 2,05 m Stackability, empty: NA pallets high	
Raw material		
Raw material options: PP Hot filling: 85-95° C	Masterbatch colours: Colours according to RPC Superfos standard selected pantone colours.	
Hot temperatures: The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures	Cold temperatures: Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures	
Quality Specifications		
Approvals:	All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In	

accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life:

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

Quality information:

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Specifications are subject to change without notice. Version 10.2

Latest revision : 11/01/2013